



YOU NEED TO MEASURE THIS

CENTER OF THE HITCH PIN HOLE TO THE OUTSIDE OF THE SPARE TYRE

EXAMPLE:

The outside of your spare tyre to the center of the hitch pin hole is **300mm**

300 minus **250** = **50** plus **100 clearance** = **150**

If your tyre measures 300mm to pin you will want to select **+150mm Longer Main Bar**

← YOU WANT 50-100mm CLEARANCE →

BIKES FOOT PEGS 550mm ACROSS

THIS AQUA RECTANGLE REPRESENTS YOUR BIKES FOOT PEGS
APPROXIMATE AVERAGE WIDTH

250mm

550mm

STANDARD LENGTH

OUR STANDARD LENGTH ADVENTURE MAIN BAR IS:
HITCH PIN HOLE TO CENTER BIKE = 550mm
HITCH PIN HOLE TO BIKES INSIDE PEG = 250mm

RACK N ROLL HITCH MOUNTED MOTORCYCLE CARRIER ADVENTURE MAIN BAR STANDARD DIMENSIONS

HOW TO SELECT THE CORRECT LENGTH MAIN BAR FOR YOUR SUV WITH A REAR MOUNTED SPARE TYRE OR OTHER ACCESSORIES

ALL COPYRIGHT AND OTHER PROPERTY RIGHTS CONTAINED HEREIN ARE THE PROPERTY OF RACK N ROLL PTY LTD AND ARE NOT TO BE COPIED, REPRODUCED OR DISTRIBUTED WITHOUT PRIOR WRITTEN CONSENT OF RACK N ROLL PTY LTD